

TECHNICAL SPECIFICATION LED Spotlights SA-913



Technical data

- Nominal voltage: 230V/50Hz
- Power: 3W
- Colour temperature: 2700K / 4000K
- Power Supply: Low Voltage, DC device
- LEDs: High power
- Beam Angle: 60°
- Colour rendering index: Ra≥80
- Average Lifetime: 30 000h
- Switch on/off > 15 000
- Non dimmable
- Housing: aluminum casting 90x50mm
- Protection against dust and moisture: IP21
- Color: gold/graphite

Product benefits:

- Energy-saving fixture in replacement of halogen downlights
- Safety, low voltage operation
- Installation in suspended ceilings
- Comfort atmosphere of homogeneous light distribution
- Instant light with maximum luminous flux
- Low power consumption
- Repeated switch on/off does not affect the lifespan
- Instant light with maximum luminous flux
- Environmentally friendly - no mercury and lead

Areas of application:

- Commercial
- Administrative buildings
- Residential buildings
- Banks
- Hospitals
- Schools

Variants and dimensions:

Watt	Colour	LED lamp lumens (lm)	Colour temp. (K)	Size (mm)		Catalogue number
				Diameter	Height	
3W	gold	240	4000-4300	90	50	92913WH/G
3W	gold	240	2700-3000	90	50	92913WW/G
3W	graphite	240	4000-4300	90	50	92913WH/GR
3W	graphite	240	2700-3000	90	50	92913WW/GR

Energy efficiency:

