

TECHNICAL SPECIFICATION

LED STRIP

LED 600 SMD3528 IP20



Technical data

- Rated voltage : 12V DC
- Power consumption: 9.6W/m
- Luminous efficiency: 6-7lm/LED
- Number of LEDs: 120pcs/m
- LED type: SMD3528
- Light source: Epistar Taiwan
- Colour temperature:
 - LED-3528-120-WW - 2700-3000K; warm white
 - LED-3528-120-CW - 6200-6500K; cold white
- Length: 5m/reel
- Cut option: per 25mm
- Beam angle: 120°
- Protection against dust and moisture: IP20
- Average lifetime: 30000h


Areas of application

- Domestic application
- Accent lighting
- Landscape lighting
- Shops
- Pathways

Product benefits


- Easy to install.
- Low energy consumption.
- Mercury free.
- Correct operation even at low temperature.
- Instant-on light.
- Long lifetime.

Variants and dimensions



Model	LEDs (pcs/m)	Watt / metter	Colour temp. (K)	Catalogue number	Packing (reel)
LED-3528-120-WW	120pcs/m	9.6W/m	2700-3000	99LED666	1
LED-3528-120-CW	120pcs/m	9.6W/m	6200-6500	99LED667	1

Energy efficiency



Barcodes

Barcode	Catalogue number
3800131187413	99LED666
3800131187420	99LED667

Standards

EN 62031

