

TECHNICAL SPECIFICATION

LED Cabinet Light – CAB-14



Technical data

- Power: 2.4W
- Color temperature: white / warm white
- Rated voltage: 12VDC
- Power Supply: control gear – driver for 12VDC (not included in the set)
- Type of LED: SMD3528
- Light source: Epistar Taiwan
- Luminous flux: 210lm
- Protection against dust and moisture: IP20
- Housing: ABS 57x57x10mm
- Colour of the housing: silver
- Diffuser: polycarbonate
- Long life : 30000h
- Beam angle: 120°
- Colour rendering index: Ra≥80


Areas of application

- Kitchen facilities
- Service areas
- Residential buildings
- Retail Showcases and counters

Product benefits


- Safety, low voltage operation
- Uniform and gentle illumination
- Low power consumption
- Repeated switch on/off does not affect life span
- Instant light with maximum luminous flux
- Environmentally friendly - no mercury and lead
- No ultraviolet and infrared rays

Variants and dimensions




Watt	Lumen (lm)	Colour temp.	Colour body	Size			Catalogue number	Packing (pcs)
				Length	Width	Height		
2.4W	210	white	silver	57	57	10	914LED02	100
2.4W	210	warm white	silver	57	57	10	914LED12	100


Energy efficiency




This lighting fixture contains built in led lamps from energy classes.

The lamps in the lighting fixture cannot be changed.







914LED02

874/2012

Barcodes

Barcode	Catalogue number
3800131185648	914LED02
3800131185655	914LED12

Standards

EN 60598-1

EN 60598-2-1

EN 55015

EN 61547

EN 61000-3-2

